




# CEILING RECESSED TRIM

POSSIBLE CUSTOM SHAPES :






GENERAL SPECIFICATION

DIMENSION	Made to measure : - overall size: width 0.6 to 12.0 in (15.24 x 304.8 mm) length 4.0 to 120.0 in (101.6 x 3048.0 mm)
COLOUR TEMPERATURES	 2700 K  3200 K  3500 K  4100 K  5000 K  Tunable white  RGB  RGB +W and other K under request
INPUT VOLTAGE	24V DC
DRIVER	AC DC 24V DC OUTPUT (class 2 Power Unit)
DIMMABILITY	by all existing systems
POWER CONSUMPTION	Standard bright 4.5 W per linear ft (14 W per linear mt) High bright 9.0 W per linear ft (28 W per linear mt)
WEIGHT	5.7 lbs/sq. ft (25 Kg/sq. mt)
IP GRADE	IP40
LUMEN DELIVERED	Standard bright 280 lm per linear ft (890 lm per linear mt) High bright 570 lm per linear ft (1632 lm per linear mt)
LIFE TIME	70.000 hrs
WARRANTY	3 Years (36 month)
CERTIFICATIONS	<ul style="list-style-type: none"> <li>• Ceiling surface Mounted</li> <li>• Ceiling recessed Type IC Inherently protected</li> <li>• Wall surface Mounted</li> <li>• NEW Storage Area of a Clothes Closet</li> <li>• UL94 (in accordance with the requirements of ASTM E 84, ANSI / UL 723, or CAN / ULC-S102)*</li> </ul>  


\* to be asked at the order time if needed.







# *Springs*

TYPE OF FIXING	RECESSED TRIM
NAME OF FIXING SYSTEM	<b>SPRINGS</b>
BACKLIGHT MODELS ABLE TO BE FIXED BY SPRINGS	PRO
DIMENSION	Overall size: width 0.6 to 6.0 in (15.24 to 152.4 mm) length 4.0 to 120.0 in (101.6 to 3048.0 mm)

## EXAMPLE OF SECTION : 2.2 in (55.88 mm) WIDE PRO







# WARNINGS



DO NOT WET



DO NOT USE DETERGENTS



DO NOT USE HUMID FABRICS