# UNIFORM LIGHTING FRAMES



SACKLIGHT
Designed and Made in Italy



### Index

- 04 | What is HALO
- 05 | **Size**
- 06 | Technical specs
- 07 | Sections
- 08-09 | Ceiling & Wall recessed by magnets and iron plate
  - 10-11 | Installation manual | Ceiling & Wall recessed
  - 12-13 | Ceiling & Wall surface by magnets and iron plate
  - 14-15 | Installation manual | Ceiling & Wall surface

## HALO

#### The architecture of light.


The Backlight HALO line is a versatile and elegant lighting solution designed to create a perimeter lighting effect. Its main uses include lighting around mirrors, elevator lighting, and more generally, can be installed on both walls and ceilings, as well as used as suspensions.

These lamps are produced in a single, custom-made piece, with the possibility of being made in irregular shapes.


The lamps in the HALO line stand out from other similar products for their construction that avoids the visibility of common joints normally present at the corners.

Thanks to this, HALO guarantees perfect light uniformity and an impeccable result. It is possible to choose the color temperature of the light among various available options, customizing the light according to design needs and creating a perfect atmosphere for every occasion.

#### **Sizes**



Available in custom width under request




#### **Technical Specs**


COLOR TEMPERATURE	2000 K 2700 K 3000 K 3500 K 4100 K 5000k
	Tun. White Tun. White Custom range 2000-6500K Tun. White*  RGB RGBW*  RGBWW*  DIM to WARM*
	*Under request for a minimum order quantity to be define.
CRI	> 95
INPUT VOLTAGE	24VDC
DRIVER	AC DC 24V DC OUTPUT (class 2 Power Unit)
DIMMABILITY	by all existing systems (ELV/MLV, 0-10V, DALI, LUTRON, DMX)
POWER CONSUMPTION	14 W per linear mt (4,5 W per linear ft) of perimeter
LUMEN DELIVERED	890 lm per linear mt (280 lm per linear ft) of perimeter
IP GRADE	IP40 for Dry Location (IP54 for Damp Location under request)
DIMENSIONS	Short side   MM 203.2 to 2006.6 mm   INCHES 8.0 to 79.0 in
	Long side   MM 1101.6 to 3048.0 mm   INCHES 4.0 to 120.0 in
	Width of light       15.24 mm (0.6")       30.48 mm (1.2")       40.64 mm (1.6")       76.2 mm (3")       152.4 mm (6")         25.4 mm (1")       35.56 mm (1.4")       50.8 mm (2")       101.6 mm (4")       203.2 mm (8")
LIFE TIME	70.000 hrs
WARRANCY	3 Years (36 month)
CERTIFICATIONS	C€ EHI cUlus 🐨

#### **Sections**

**RECESSED MOUNTING** by magnets and iron plate



#### **SURFACE MOUNTING** by magnets and iron plate






#### **CEILING RECESSED MOUNTING**

By magnets and iron plate

**WALL RECESSED MOUNTING**By magnets and iron plate





#### INSTALLATION MANUAL | HALO WALL & CEILING RECESSED MOUNTING by magnets and iron plate



Note: The cup of screws must be less deep then 3mm.

#### INSTALLATION MANUAL | HALO WALL & CEILING RECESSED MOUNTING by magnets and iron plate





#### **CEILING SURFACE MOUNTING**


By magnets and iron plate

WALL SURFACE MOUNTING

By magnets and iron plate




#### INSTALLATION MANUAL | HALO WALL & CEILING SURFACE MOUNTING by magnets and iron plate




Note: The cup of screws must be less deep then 3mm.


#### INSTALLATION MANUAL | HALO WALL & CEILING SURFACE MOUNTING by magnets and iron plate























Discover all our most famous products that have made and still make lighting history.

MAGIC CLOUD Custom Uniform Lighting Panels

**FLUSH** Custom Uniform Lighting Bars

HALO Custom uniform Lighting Frames in a single piece

**HIDE** Line of Uniform Lighting Circles

PILL Plasterboard built-in Square and Round Lights

**WETTY** WET / IP67 Line

**CHIARO** Lighting Integration for ARMSTRONG CEILINGS

**STAMP** Creative light on plasterboard



www.backlightsrl.com

#### *⇒*ACKLIGHT

Via Alessandro Volta, 5 20876 Ornago (MB) Italy

+39 039 6010396 www.backlightsrl.com info@backlightsrl.com

