


STANDARD SIZES



Standard 1	ı
------------	---

15 x 15 IN 381 x 381 mm

PLASTERBOARD by Backlight 14.88 x 14.88 IN 378 x 378 mm

12 x 12 IN 304.8 x 304.8 mm Standard 2

15 x 30 IN 381 x 762 mm

PLASTERBOARD by Backlight 14.88 x 29.88 IN 378 x 759 mm

12 x 27 IN 304 8 x 685 8 mm Standard 3

SURFACE CUT 23 x 23 IN 584.2 x 584.2 mm


PLASTERBOARD by Backlight 22.87 x 22.87 IN 581 x 581 mm

20 x 20 IN 508 x 508 mm


SECTION


ACKLIGHT STAMP panels can be integrated with all existing thicknesses of plasterboard sheets.

VERSION FOR SHEETS 12,5 mm thick (1/2 IN)



VERSION FOR SHEETS 16 mm thick (5/8 IN)






TECHNICAL SPECIFICATION



Using 4 Backlight STAMP Performance on a room of 3 x 3 x h 2,7 meters (10 x 10 x h 8,85 FT)





INPUT VOLTAGE | 24V DC

CASE STUDY

WATTAGE | Between 18 and 30 W depending on the model

LUMENS | Between 1200 and 2000 lm delivered depending on the model

KELVIN | 2700 K, 3000K, 4000K, 5000K

Tunaple white 2000-6500K

RGBW, RGBTW and DIM TO WARM

CRI | >95 (Dim to Warm >90)

IP RATING | IP40 (Dry location)

IK RATING | IK 10

LIFE TIME | 70.000 hrs at 25° C

Standard lighting shapes of STAMP Performance line



STAR




DROP





HEART









INITIALS

Your **signature**, your **habitat**.



ICON

Your lighting accent for all situations.







ABAT JOURS





CREATIVITY

Free your imagination!







CUSTOMIZE THE SIZE

In addition to the standard sizes **Backlight Stamp** can also be made to measure.

Case study



MAXIMUM CUSTOMIZATION

Your texture on our Backlight STAMP.



1 Plasterboard by Backlight



3 Send us your HR file in JPEG format




2 Choose your lighting shape and send us the right vector file




4 Customized ACKLIGHT STAMP

Installation manual


- 1 Cut your plasterboard surface using the supplied template.
- 2 Remove, if there, the metal parts in order to leave void space.




- **3** Bring out of the hole the extending cable coming from the 24VDC remote driver.
- **4** Position the supplied clips on the rear side of your existing plasterboard the kit includes different type of clips; use only the ones that match with your plasterboard thickness.




5 - Screw the clips.




6 - Connect the cable and position your **SACKLIGHT STAMP**




7 - Screw ACKLIGHT STAMP on the clips.



9 - Once the plaster is dry, paint your surface.



8 - Apply the adhesive mesh (not supplied) along the joints and plaster to get an uniform an leveled surface.



10 - Remove the protective film when the paint is still wet.



△ACKLIGHT

Via Alessandro Volta, 5 20876 Ornago (MB) Italy

+39 039 6010396 www.backlightsrl.com info@backlightsrl.com

